





ENVIRONMENTAL LAND SOLUTIONS, L
Landscape Architecture and Environmental Planning

8 KNIGHT STREET, SUITE 203 NORWALK, CONNECTICUT 06851

Tel: (203) 855-7879 Fax: (203) 855-7836 info@eislic.net www.eislic.net

Regulatory Approval Submission Set Baywater Housing Partners 26 East Lane Darien CT

	Project Team:		List of Drawings		Baywater Housing
Ti	ngineers ghe & Bond 000 Bridgeport Avenue				Partners
	uite 320		SHEET INDEX		
51	helton, CT 06484	ם	Name		26 East Lane
20	03.712.1100	CS CS	Cover Sheet		
		CO.1	GENERAL NOTES, LEGEND AND STANDARD ABBREVIATIONS PLAN		
		C1.0	SITE PLAN		
₹ .		C1.1	PROPOSED DRIVEWAY PROFILE		
	rchitect	C2.0	GRADING PLAN		
	aniel Conlon Architects	C3.0	DRAINAGE AND UTILITY PLAN		Darien, CT
	Old Mill Road P.O. Box 418	C4.0	SOIL EROSION AND SEDIMENT CONTROL PLAN		, -
d G	eorgetown CT 06829	C4.1	SOIL EROSION AND SEDIMENT CONTROL DETAILS		
ğ 20	03-544-7988	C5.0	SITE DETAILS		VERIFY SCALE
E BUI		C5.1	SITE DETAILS		BAR IS 1 INCH ON ORIGINAL DRAWING
TLAN		C5.2	STORM DETAILS		0 1 INCH
SEAS		C5.3	STORM DETAILS		IF NOT ONE INCH ON THIS SHEET, ADJUST
la l	andscape Architect	C5.4	SANITARY DETAILS		SCALES ACCORDINGLY
	nvironmental Land Solutions, LLC	C5.5	WATER SERVICE DETAILS		
8	Knight Street, Suite 203	LPT	LANDSCAPE PLAN		
	orwalk, CT 06851	A-1	FLOOR PLANS		
	03-855-7879	A-2	2ND FLOOR PLANS		
6/Dra		A-3	ELEVATIONS FRONT-RIGHT		
DB 15.		A-4	ELEVATIONS REAR-LEFT		MARK DATE DESCRIPTION
st La		B-1	FLOOR PLANS		PROJECT NO: 5-25-18
Se Es		B-2	2ND FLOOR PLANS		FILE: DRAWN BY:
enove		В-3	ELEVATIONS FRONT-RIGHT		CHECKED:
DCAG		В-4	ELEVATIONS REAR-LEFT		APPROVED:
ed/Current Jobs I					5045
s/Shar				-	SCALE: 1:0.83
Nolume					CS

A. GENERAL NOTES

- 1. THESE DRAWINGS ARE RELEASED FOR REVIEW BY THE TOWN OF DARIEN, AND ARE NOT RELEASED FOR CONSTRUCTION
- 2. INFORMATION TAKEN FROM MAPS TITLED ZONING LOCATION AND TOPOGRAPHIC SURVEY, 26 FAST LANE, PREPARED FOR SAYWATER HOUSING PARTNERS, LLC, DARIEN CONNECTICUT, DATED MARCH 18TH 2018, REVISED MAY 16, 2018, AND PREPARED BY WILLIAM W. SEYMOUR & ASSOCIATES, P.C.
- 3. IT IS THE DEVELOPER'S RESPONSIBILITY TO OBTAIN ALL NECESSARY PERMITS AND/OR EASEMENTS FROM STATE AND LOCAL AUTHORITIES AND ANY CONSTRUCTION RIGHTS AND/OR SLOPE RIGHTS AS MAY BE REQUIRED FORM THE PROPERTY OWNERS.
- 4. IT IS THE CONTRACTOR'S RESPONSIBILITY TO ASSURE THAT ALL PIPING IS PROPERLY BEDDED AND STABILIZED IN AREAS OF HIGH GROUND WATER AND/OR UNSTABLE SOIL CONDITIONS.
- 5. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH TOWN OF DARIEN AND/OR CONNECTICUT DEPARTMENT OF TRANSPORTATION
- ANY DRAINAGE STRUCTURES, DITCHES, ASPHALT, CURBS, OTHER EXISTING CONSTRUCTION OR GRASSED AREAS DISTURBED DURING CONSTRUCTION SHALL BE RESTORED TO THE ORIGINAL CONDITION.
- A ROAD-OPENING PERMIT FOR WORK WITHIN A TOWN ROAD RIGHT-OF-WAY IS TO BE ACQUIRED FROM THE TOWN'S HIGHWA DEPARTMENT. ALL WORK WITHIN TOWN ROAD RIGHT-OF-WAY IS TO BE APPROVED AND COMPLETED TO THE SATISFACTION OF THE TOWN HIGHWAY DEPARTMENT.
- 8. ALL PROPOSED SIGNS SHALL CONFORM TO SECTION 8.E.2 OF THE TOWN OF DARIEN ZONING REGULATIONS
- 9. FIRE LANE MARKINGS SHALL BE STRIPED IN THE FIELD PER FIRE MARSHAL REVIEW AND DIRECTION IF REQUIRED.
- 10. HANDICAPPED PARKING SHALL CONFORM TO A.D.A. CRITERIA. REMAINDER OF THE SITE DESIGN SHALL CONFORM TO THE TOWN OF DARIEN ZONING REGULATIONS.
- 11. ALL SITE LIGHTING SHALL CONFORM TO THE TOWN OF DARIEN ZONING REGULATIONS SECTION 8.C.7
- 12. VERTICAL DATUM IS NAVD 88.

B. UTILITY COORDINATION NOTES

- UTILITY LOCATIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO FINAL SITE SURVEY. IT IS THE RESPONSIBILITY OF THE
 CONTRACTOR TO VERIFY ALL ELEVATIONS, PROPERTY LINES, LOCATION OF UTILITIES AND SITE CONDITIONS IN THE FIELD. IF AN
 UNFORESEEN INTERFRENCE EXISTS BETWEEN AN EXISTING AND A PROPOSED STRUCTURE, THE CONTRACTOR SHALL NOTIFY THE DESIGN ENGINEER SO THAT THE APPROPRIATE REVISIONS CAN BE MADE.
- 2. IT IS THE RESPONSIBILITY OF EACH BIDDER IN EVALUATING THESE PLANS TO MAKE EXAMINATIONS IN THE FIELD BY VARIOUS METHODS AND OBTAIN NECESSARY INFORMATION FROM AVAILABLE RECORDS, UTILITY CORPORATIONS, AND IND
- 3. THE CONTRACTOR IS TO USE CAUTION WHEN WORKING NEAR OR UNDER OVERHEAD AND UNDERGROUND UTILITIES. THE CONTRACTOR IS TO NOTIFY THE UTILITY COMPANIES OF HIS INTENT PRIOR TO THE COMMENCEMENT OF ANY WORK.
- 4. PLANTINGS SHALL NOT BE PLACED ON TOP OF UTILITIES.

C. STORM SEWER NOTES

- STORM SEWER LINES ARE TO BE INSTALLED USING INVERT ELEVATIONS, PIPE SLOPES SHOWN ARE APPROXIMATE AND ARE FOR
- 2. APPLICABLE STORM SEWER CONSTRUCTION SHALL CONFORM TO THE TOWN OF DARIEN STORM SEWER SPECIFICATIONS.
- 3. ROOF DRAINS ARE TO BE CONNECTED TO THE STORM DRAINAGE SYSTEM WHERE SHOWN.
- 4. THE ON-SITE DRAINAGE SYSTEM WILL REMAIN PRIVATE. THE PROPERTY OWNER IS TO PROVIDE REGULAR MAINTENANCE OF THE SYSTEM TO ALLOW IT TO CONTINUALLY FUNCTION AS INTENDED.
- 5. THE INSTALLATION OF THE DRAINAGE SYSTEM IS TO BE DONE LINDER THE SUPERVISION OF THE DESIGN ENGINEER LICENSED IN THE STATE OF CONNECTICUT. AFTER CONSTRUCTION, THE ENGINEER IS TO SUBMIT TO THE TOWN WRITTEN CERTIFICATION THAT THE SYSTEM WAS INSTALLED AS PER THE APPROVED DESIGN. A DRAINAGE AS-BUILT DRAWING IS SUBMITTED WITH THIS LETTER TO THE TOWN.
- 6. ALL PORTIONS OF THE STORM DRAINAGE SYSTEM ARE TO BE CAPABLE OF HANDLING AASHTO H-20 LOADS.
- 7. ALL REINFORCED CONCRETE PIPE SHALL BE CLASS IV UNLESS OTHERWISE NOTED.
- 8. ALL PVC PIPING TO BE CLASS SDR-35 UNLESS OTHERWISE NOTED
- 9. ALL CATCH BASIN GRATES TO BE TYPE A UNLESS OTHERWISE NOTED.
- 10. ALL CATCH BASINS SHALL HAVE BELL TRAPS EXCEPT IF CONNECTED IN A SERIES, IN WHICH CASE ONLY THE UPPER TWO CATCH BASINS IN THE SERIES SHALL HAVE BELL TRAPS.
- 11. HDPE PIPING SHALL CONFORM TO ASTM F2306

D. SANITARY SEWER & WATER NOTES

- 1. SANITARY SEWER AND WATER LINE CROSSINGS SHALL MAINTAIN AN 18 INCH MINIMUM VERTICAL SEPARATION DISTANCE.
- 2. SEWER AND WATER LINE CROSSING ALL OTHER UTILITIES SHALL MAINTAIN A 12 INCH VERTICAL SEPARATION DISTANCE.
- SANITARY SEWER LINES ARE TO BE INSTALLED USING INVERT ELEVATIONS. PIPE SLOPES SHOWN ARE APPROXIMATE AND ARE
- 4. PROPOSED SANITARY SEWER MAINS AND SANITARY SEWER SERVICES ARE TO MEET THE REQUIREMENTS OF THE TOWN OF DARIEN. AFTER ACCEPTANCE, THE MAINS SHALL BE TURNED OVER TO THE TOWN.
- 5. PROPOSED WATER SERVICES ARE TO MEET THE REQUIREMENTS OF THE STATE PLUMBING CODES AND THE AQUARION WATER
- 6. ALL SEWAGE DISCHARGES MUST BE CONSISTENT WITH THE TOWN OF DARIEN'S CURRENT NPDES PERMIT

E. GRADING NOTES

- 1. AREAS OF DISTURBED EARTH SHALL BE STABILIZED BY MULCHING OR OTHER MEANS. SEEDING OF GRASSED AREAS SHALL BE INITIATED AS SOON AS PRACTICAL AS AN EROSION AND SILTATION CONTROL MEASURE
- 2. WHERE LEDGE IS TO BE LEFT IN PLACE. THE STABILITY OF THE LEDGE IS TO BE VERIFIED BY A QUALIFIED STATE OF CONNECTICUT LICENSED PROFESSIONAL ENGINEER OR SOIL SCIENTIST

ABBREVIATIONS

AASHTO - AMERICAN ASSOCIATION OF STATE HIGHWAY & TRANSPORTATION OFFICIALS ACI - AMERICAN CONCRETE INSTITUTE

A.D. - ANGLE OF DEFLECTION

A.D.A. - AMERICANS WITH DISABILITIES ACT

ALUM: - ALUMINUM BC - BOTTOM OF CURB BIT - BITUMINOUS

BIT - BITUMINOUS BW - BOTTOM OF WALL CB - CATCH BASIN CONC - CONCRETE DIA - DIAMETER DIP - DUCTILE IRON PIPE

DMH - DRAINAGE MANHOLE

EA - EACH

EA - EACH
EL - ELEVATION
ELEV - ELEVATION
EW - ENDWALL
EXIST. - EXISTING
EXP. - EXPANSION

FT - FEET GR - GRATE

HDPE - HIGH DENSITY POLYETHYLENE PIPE

HOR. - HORIZONTAL HP - HIGH POINT

HW - HEADWALL HYD - HYDRANT

HYD - HYDRANI INV - INVERT LF - LINEAR FEET A. - MAXIMUM MEG - MEET EXISTING GRADE

MH - MANHOLE

NGVD29 - NATIONAL GEODETIC VERTICAL DATUM OF 1929

O.C. - ON CENTER O.D. - OUTSIDE DIAMETER

O.D. - OUTSIDE DIAMETER
PC - POINT OF CURVATURE
PROP - PROPOSED
P.S.I. - POUNDS PER SOUARE INCH
PT - POINT OF TANGENCY OR POINT
PVC - POLYVINIV. CHLORIDE PIPE OR POINT OF VERTICAL CURVATURE
PVI - POINT OF VERTICAL INFLECTION
PVMT - PANCEMENT

PVMT. - PAVEMENT
PVT - POINT OF VERTICAL TANGENCY


RCP - REINFORCED CONCRETE PIPI

RCP - REINFORCED CONCRE
RL - ROOF LEADER
ROW - RIGHT OF WAY
SF - SOUARE FEET
SQ. - SQUARE
SMH - SANITARY MANHOLE
STA - STATION
TC - TOP OF CLUPP

TC - TOP OF CURB

TW - TOP OF WALL TYP. - TYPICAL

VC - VERTICAL CURVE VERT. - VERTICAL WT. - WEIGHT YD - YARD DRAIN



LOCATION MAP SCALE: 1"=600"

LEGEND

DESCRIPTION	EXISTING	PROPOSED
PROPERTY LINE		
EASEMENT LINE		
PROJECT LIMIT LINE		
FENCE	o	
MINOR CONTOUR		
MAJOR CONTOUR		00
SPOT ELEVATION	+219.4	× 36.3
TREES	(312"OA	
EDGE OF PAVEMENT		
CONCRETE CURB LINE		
WHITE PAINTED LINES		
BUILDING		
WALL	000000000000000000000000000000000000000	
ENDWALL		
WATER QUALITY STRUCTURE	⊜ ⊜	000
STORM SEWER	12"	
STORM MANHOLE	0	
CATCH BASIN	CB	
YARD DRAIN		
DEEP TEST HOLE	+	
UNDERGROUND ELECTRIC	Ε	E
ELECTRIC MANHOLE	©	0 0
LIGHT POLE	\$\text{LP}	
UTILITY POLE	SNET -0- #754	
SANITARY SEWER	10°8	ss
SANITARY LATERAL		ss
SANITARY MANHOLE	SMH S	<u>s</u>
FIRE SERVICE		F-HP
WATER MAIN		PW
WATER METER		(00)
WATER VALVE	WV °	
HYDRANT		<u></u>
TEL-DATA - BURIED		
TEL-DATA MANHOLE	(T)	0
FUEL TANK		
GUIDERAIL		
SIGN & SIGN POST		
SIDEWALK	CONCRETE WALK	
HANDICAP PARKING	&-	
YELLOW PAINT LINE	<u></u>	
STOP BAR		+
LIGHT		*
INFILTRATION SWALE		
WETLAND LIMIT		
WETLAND FLAG	13▷	
WETLAND BUFFER	——— vв ——— vв ———	

EVICTING

DDODOSED

Shelton CT 06484 (203) 712-1100

DANIEL CONLON ARCHITECT 4 Old Mil Road



NVIRONMENTAL LAND SOLUTIONS, LL

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsllc.net www.elsllc.net





Baywater Housing **Partners**

26 East Lane


Darien, CT

VERIFY SCALE BAR IS 1 INCH ON

SCALES ACCORE

GENERAL NOTES, LEGEND AND STANDARD ABBREVIATIONS PLAN

C_{0.1}



Tighe&Bond
Engineers | Environmental Specialist

1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100





ENVIRONMENTAL LAND SOLUTIONS, LLC
Landscape Architecture and Environmental Planning

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsllc.net www.elsllc.net





Baywater Housing Partners

26 East Lane

Darien, CT

VERIFY SCALE


BAR IS 1 INCH ON
ORIGINAL DRAWING
O
IF NOT ONE INCH ON
THIS SHEET, ADJUST
SCALES ACCORDINGLY

MARK	DATE	DESCRIPTION			
PROJE	CT NO:	B0509-007			
DATE: MAY 25, 2018					
FILE:	B0509-07-C-1	00-SITE.dwg			
DRAW	DRAWN BY: MDS				
CHECK	ED:	EWL			
APPRO	VED:	JWB			

SITE PLAN

ALE: 1

C1.0





1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100

DANIEL CONLON
ARCHITECTS
ARCHITECTS
405 BRAG
405 BAT-766
PO. Birt 118, Georgian CT 9823
ACCOUNT ACTION ACCOUNT ACTION ACCOUNT ACCOUNT



ENVIRONMENTAL LAND SOLUTIONS, LLC Landscape Architecture and Environmental Planning

8 KNIGHT STREET, SUITE 203 NORWALK, CONNECTICUT 06851

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsllc.net www.elsllc.net





Baywater Housing Partners

26 East Lane

Darien, CT

VERIFY SCALE

BAR IS 1 INCH ON
ORIGINAL DRAWING

1 INCH
IF NOT ONE INCH ON
THIS SHEET, ADJUST
SCALES ACCORDINGLY

DATE DESCRIPTION

1 NO: 80509-007

MAY 25, 2018

PROJECT NO: B0509-007

DATE: MAY 25, 2018

FILE: B0509-07-C-110-PROF.dwg

DRAWN BY: MDS

CHECKED: EWL


PROPOSED DRIVEWAY PROFILE

SCALE: AS N

C1.1

Last Saved: 5/5/2018 Plotted On: May 22, 2018-4: 56pm By: JCB1

HORIZONTAL SCALE 1" = 20'
20'
40'
VERTICAL SCALE 1" = 4'





1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100





ENVIRONMENTAL LAND SOLUTIONS, LLC
Landscape Architecture and Environmental Planning

8 KNIGHT STREET, SUITE 203

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsllc.net www.elsllc.net





Baywater Housing Partners

26 East Lane

Darien, CT

VERIFY SCALE


BAR IS 1 INCH ON
ORIGINAL DRAWING
1 INCH
IF NOT ONE INCH ON
THIS SHEET, ADJUST


RK DATE	DESCRIPTION			
DJECT NO:	B0509-007			
TE:	MAY 25, 2018			
E: B0509-07-C-200-GRAD.dwg				
AWN BY:	MDS			
CKED:	EWL			
ROVED:	JWB			

GRADING PLAN

CALE: 1" = 2

C2.0





SEDIMENTATION & EROSION CONTROL

THE STORMWATER MANAGEMENT MEASURES, WILL ADDRESS THE STORMWATER QUALITY ONCE THE SITE HAS BEEN CONSTRUCTED AND STABILIZED. SEDIMENTATION AND EROSION CONTROL MEASURES WILL BE INSTALLED DURING CONSTRUCTION WHICH WILL MINIMIZE ADVERSE IMPACTS FROM CONSTRUCTION ACTIVITIES

SEDIMENTATION AND EROSION CONTROL MEASURES PROPOSED FOR THIS DEVELOPMENT HAVE BEEN DESIGNED IN ACCORDANCE WITH THE "2002 CONNECTICUT GUIDELINES FOR SOIL EROSION AND SEDIMENTATION CONTROL" AS PUBLISHED BY THE CONNECTICUT COUNCIL ON SOIL EROSION AND WATER CONSERVATION. ADDITIONAL GUIDELINES HAVE ALSO BEEN FOLLOWED THAT ARE AVAILABLE FROM THE CONNECTICUT DEPARTMENT OF ENVIRONMENTAL PROTECTION AS RECOMMENDED FOR SEDIMENTATION CONTROL DURING CONSTRUCTION

LISTED BELOW ARE THE EROSION CONTROL NARRATIVE AND THE EROSION CONTROL NOTES.

EROSION CONTROL NARRATIVE

GENERAL


- 1. THE PROPOSED DEVELOPMENT IS ENTITLED "26 EAST LANE" IN DARIEN, CONNECTICUT.
- ESTIMATED: PROJECT START: SPRING 2019
- EROSION CONTROL NARRATIVE REFERS TO DRAWING C4.0.
- THE PROPOSED SITE DEVELOPMENT WILL CONSIST OF CLEARING AND GRUBBING THE EXISTING SITE, EXCAVATION AND ROUGH GRADING OF ROADWAYS, PARKING AREAS, SIDEWALKS AND CURBING.
- THE DEVELOPMENT IS LOCATED IN DARIEN, CONNECTICUT AND IS LOCATED ON EAST LANE

CONSTRUCTION SEQUENCE

- 1. FLAG THE LIMITS OF CONSTRUCTION, RIGHT-OF-WAY AND TREE PROTECTION ZONES.
- HOLD PRECONSTRUCTION MEETING. (REMEMBER TO CALL BEFORE YOU DIG 1-800-922-4455).
- 3. HOLD TREE CUTTING MEETING
- 4. INSTALL THE CONSTRUCTION ENTRANCE.
- INSTALL PERIMETER EROSION AND SEDIMENT CONTROLS AND TREE PROTECTION DEVICES IN ACCORDANCE WITH THE SESC PLAN.
- EXCAVATE ALL STUMPS LOCATED IN THE BUILDING FOOTPRINT, PARKING AREAS AND ROADWAY AND REMOVE TO A DISPOSAL SITE OR STOCKPILE AREA TO BE CHIPPED. REMAINING STUMPS SHALL BE GROUND IN PLACE.
- DEMOLISH EXISTING BUILDINGS.
- MAKE ALL CUTS AND FILLS REQUIRED. ESTABLISH THE SUB-GRADE FOR THE TOPSOIL AREAS, PARKING AND ROADWAY AS REQUIRED AND BENCH THE BUILDINGS TO A SUBGRADE. ALLOW A REASONABLE AMOUNT OF AREA AROUND THE FOOTPRINT OF THE BUILDINGS FOR THE CONSTRUCTION ACTIVITIES.
- BEGIN CONSTRUCTION OF THE BUILDINGS.
- 10. INSTALL ALL SANITARY SEWERS AND DRAINAGE FACILITIES STARTING AT THE OUTFALL AND
- ENSURE DISCHARGE LOCATIONS ARE STABLE. IF NOT STABLE, REVIEW DISCHARGE CONDITIONS WITH THE DESIGN ENGINEER AND IMPLEMENT ADDITIONAL STABILIZATION MEASURES PRIOR TO INSTALLING WATER SURFACE CONTROLS.
- 12. PREPARE SUB-BASE, SLOPES, PARKING AREAS, SHOULDER AREAS, AND ANY OTHER AREA OF
- 13. INSTALL PROCESS AGGREGATE IN PARKING AREAS
- 14. PLACE TOPSOIL WHERE REQUIRED. COMPLETE THE PERIMETER LANDSCAPE PLANTINGS.
- 15. FINE GRADE, RAKE, SEED AND MULCH TO WITHIN 2 FEET OF THE CURBING.
- 16. UPON SUBSTANTIAL COMPLETION OF THE BUILDINGS, COMPLETE THE BALANCE OF SITE WORK AND STABILIZATION OF ALL OTHER DISTURBED AREAS. INSTALL FIRST COURSE OF
- WHEN ALL OTHER WORK HAS BEEN COMPLETED, REPAIR AND SWEEP ALL PAVED AREAS FOR THE FINAL COURSE OF PAVING. INSPECT THE DRAINAGE SYSTEM AND CLEAN AS NEEDED.
- 18. INSTALL FINAL COURSE OF PAVEMENT FOR PARKING AREAS AND ROADWAY
- 19. AFTER SITE IS STABILIZED, REMOVE TEMPORARY EROSION AND SEDIMENT CONTROLS (E.G. GEOTEXTILE SILT FENCES AND HAYBALES)

EROSION CONTROL NOTES

- ALL SEDIMENTATION AND EROSION CONTROL MEASURES SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE STANDARDS AND SPECIFICATIONS OF THE "2002 CONNECTICUT GUIDELINES FOR SOIL FROSION AND SEDIMENT CONTROL", DEP BUILLETIN NO. 34, AND ALL AMENDMENTS AND ADDENDA THERETO AS PUBLISHED BY THE CONNECTICUT DEPARTMENT
- LAND DISTURBANCE SHALL BE KEPT TO THE MINIMUM NECESSARY FOR CONSTRUCTION
- ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AS SHOWN ON THE PLAN AND ELSEWHERE AS ORDERED BY THE ENGINEER OR THE TOWN
- ALL CATCH BASINS SHALL BE PROTECTED WITH A SILT SACKS, HAYBALE RING, SILT FENCE OR BLOCK AND STONE INLET PROTECTION THROUGHOUT THE CONSTRUCTION PERIOD AND UNTIL ALL DISTURBED AREAS ARE THOROUGHLY STABILIZED.
- WHENEVER POSSIBLE, EROSION AND SEDIMENT CONTROL MEASURES SHALL BE INSTALLED PRIOR TO CONSTRUCTION. SEE "EROSION CONTROL NARRATIVE".
- ADDITIONAL CONTROL MEASURES SHALL BE INSTALLED DURING THE CONSTRUCTION PERIOD AS ORDERED BY THE ENGINEER.
- ALL SEDIMENTATION AND EROSION CONTROL MEASURES SHALL BE MAINTAINED IN EFFECTIVE CONDITION THROUGHOUT THE CONSTRUCTION PERIOD
- SEDIMENT REMOVED SHALL BE DISPOSED OF OFF SITE OR IN A MANNER AS REQUIRED BY THE ENGINEER.
- THE CONSTRUCTION CONTRACTOR SHALL BE RESPONSIBLE FOR CONSTRUCTION AND MAINTENANCE OF ALL CONTROL MEASURES THROUGHOUT THE CONSTRUCTION PERIOD.
- 10. ALL DISTURBED AREAS TO BE LEFT EXPOSED FOR MORE THAN 30 DAYS SHALL BE PROTECTED WITH A TEMPORARY VEGETATIVE COVER. SEED THESE AREAS WITH PERENNIAL RYEGRASS AT THE RATE OF 40 LBS. PER ACRE (1 LB. PER 1,000 SQ. FT). APPLY SOIL AMENDMENTS AND MULCH AS REQUIRED TO ESTABLISH A UNIFORM STAND OF VEGETATION
- 11. THE CONSTRUCTION CONTRACTOR SHALL UTILIZE APPROVED METHODS/MATERIALS FOR PREVENTING THE BLOWING AND MOVEMENT OF DUST FROM EXPOSED SOIL SURFACES ONTO ADJACENT PROPERTIES AND SITE AREAS.
- 12. THE CONSTRUCTION CONTRACTOR SHALL MAINTAIN A SUPPLY OF SILT FENCE/HAYBALES AND ANTI-TRACKING CRUSHED STONE ON SITE FOR EMERGENCY REPAIR
- 13. ALL DRAINAGE STRUCTURES SHALL BE PERIODICALLY INSPECTED WEEKLY BY THE CONSTRUCTION CONTRACTOR AND CLEANED TO PREVENT THE BUILD-UP OF SILT.
- 14. THE CONSTRUCTION CONTRACTOR SHALL CAREFULLY COORDINATE THE PLACEMENT OF EROSION CONTROL MEASURES WITH THE PHASING OF CONSTRUCTION.
- 15. KEEP ALL PAVED ROADWAYS CLEAN. SWEEP BEFORE FORECASTED STORMS.
- 16. TREAT ALL UNPAVED SURFACE WITH 4" MINIMUM OF TOPSOIL PRIOR TO FINAL
- HAYBALE BARRIERS AND SILT FENCING SHALL BE INSTALLED ALONG THE TOE OF CRITICAL CUT AND FILL SLOPES.
- 18. THE CONTRACTOR SHALL NOTIFY THE TOWN OF DARIEN'S ENVIRONMENTAL OFFICIAL PRIOR TO THE INSTALLATION OF EROSION CONTROLS, CUTTING OF TREES, OR ANY EXCAVATION.
- 19. ALL TRUCKS LEAVING THE SITE MUST BE COVERED.
- 20. SOME CONTROL MEASURES ARE PERMANENT, THESE STRUCTURES SHALL BE CLEANED AND
- 21. ALL SEDIMENTATION AND EROSION CONTROLS SHALL BE CHECKED WEEKLY AND/OR AFTER EACH RAIN FALL EVENT. NECESSARY REPAIRS SHALL BE MADE WITHOUT DELAY
- 22. PRIOR TO ANY FORECASTED RAINFALL, EROSION AND SEDIMENT CONTROLS SHALL BE INSPECTED AND REPAIRED AS NECESSARY
- 23. AFTER ALL DISTURBED AREAS HAVE BEEN STABILIZED, EROSION CONTROLS MAY BE REMOVED ONCE AUTHORIZATION TO DO SO HAS BEEN SECURED FROM THE TOWN. DISTURBED AREAS SHALL BE SEEDED AND MULCHED.



SILT FENCE

SILTSACK MANUFACTURED BY

2831 CARDWELL ROAD RICHMOND, VIRGINIA 23237

SILTSACK®

NO SCALE

-DUMP STRAP

DEPTH=2

WIDTH=1.83

STABILIZE ENTIRE PILE WITH

VEGETATION OR COVER I INACTIVE FOR 30 DAYS OR MOR


MIN. SLOPE

INSTALLATION NOTES:


DUMP STRAP

1" REBAR FOR BAG

LENGTH=2.73



CONSTRUCTION ENTRANCE



TWO STAKES PER BALE

4. BACKFILL AND COMPACT EXCAVATED

MIN SLOPE

SOIL ON THE UPHILL SIDE OF THE

-DIVERT LIPSTREAM

COMPACTED BACKFILL PACKED STRAW

3. WEDGE LOOSE STRAW BETWEEN BALES TO CREATE A CONTINUOUS BARRIER

STOCKPILE

2. MAXIMUM SLOPE OF STOCKPILE SHALL BE 2H: 1V.

1. AREA CHOSEN FOR STOCKPILING OPERATIONS SHALL BE DRY AND STABLE

FENCING OR HAYBALES, THEN STABILIZED WITH VEGETATION OR COVERED.

THE WIDTH OF THE HAYBALE

BARRIER TO PREVENT PIPING PLACEMENT AND CONSTRUCTION OF HAYBALE BARRIER

Baywater Housing **Partners**

26 East Lane

1000 Bridgeport Avenue

DANIEL CONLON

ARCHITECT

NVIRONMENTAL LAND SOLUTIONS, LL

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsllc.net www.elsllc.net

4 Old Mit Road

Shelton CT 06484 (203) 712-1100

Darien, CT

VERIFY SCALE BAR IS 1 INCH ON SCALES ACCORDINGLY

MAY 25, 2018

SOIL EROSION AND SEDIMENT CONTROL

DETAILS

-ANGLE FIRST STAKE INTO 0.5 LBS/FT MIN. WEIGHT ADJACENT BALE, SECURE WITH SECOND STAKE 1.5" SQUARE HARDWOOD PACK LOOSE HAY STAKES, 36" MIN. LENGTH CATCH BASIN BETWEEN ADJACEN 0.5 LB/FT MIN BALES CROSS BRACES, AS NEEDED CATCH BASIN GRATE-FLOW 30" MAX -CTDOT No. 3 HAYBALE (TYP)-CRUSHED STONE PLACED TO ½ HEIGHT + 1/2 WIDTH OF BALE FILTER FABRIC, GEOTEX 2130 OR EQUIVALENT TUCK 6" BELOW GRADE CATCH BASIN-SILT FENCE INSTALLATION AT SECTION CATCH BASIN AT LOW POINTS HAYBALE FILTER INSTALLATION AT CATCH BASIN AT LOW POINTS


CATCH BASIN EROSION CONTROL


SOIL STOCKPILING

3. UPON COMPLETION OF SOIL STOCKPILING, EACH PILE SHALL BE SURROUNDED WITH EITHER SILT


SILT FENCE -

C4.1






FLUSH PRECAST CONCRETE CURB



VAN ACCESSIBLE




INTERNATIONAL SYMBOL OF ACCESSIBILITY

- NOTE:

 1. SIGN LOCATED AT ALL HANDICAPPED PARKING SPACES. 2. 18' X 15' D.O.T STANDARD ACCESSIBLE PARKING STALL
 3. SIGN BACKGROUND — BLUE REFLECTIVE
 4. LETTERS, GRAPHICS & BORDER — WHITE REFLECTIVE


HANDICAPPED SPACE STRIPING DETAILS





- ALL CONCRETE SHALL HAVE A MINIMUM
 COMPRESSIVE STRENGTH OF 4,000 PSI AT
 28 DAYS OR AT THE EARLIER AGE AT WHICH
 THE CONCRETE MAY BE EXPECTED TO RECEIVE
 ITS FULL LOAD.
- ALL REINFORCED CONCRETE WORK SHALL BE DONE IN ACCORDANCE WITH THE "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE", ACI 318-86, 1986 CODE AND ACI 315 "MANUAL OF STANDARD PRACTICE FOR DETAILING REINFORCED CONCRETE STRUCTURES."
- REINFORCING STEEL SHALL BE ASTM A615 DEFORMED BILLET STEEL BARS FOR CONCRETE REINFORCEMENT, GRADE 60.
- CONCRETE COVER FOR REINFORCING SHALL BE
 2", EXCEPT IN BOTTOM SLABS WHERE IT SHALL
 BE 3". OR AS OTHERWISE NOTED.


DUMPSTER PAD NO SCALE



BITUMINOUS CONCRETE LIP CURBING

TYPICAL GATE CONSTRUCTION -TYPICAL GATE CONSTRUCTION
(3) 2X6 P.T. RAILS 2X VERTICAL
STILES TO MATCH SIDING ON
ALTERNATE SIDES OF RAILS
ALL STAINLESS STEEL SCREWS,
CONNECTORS, AND OTHER
HADDWAGE. HINGES AT EACH RAIL -PROVIDE BOARD AT -PROVIDE HEAVY DUTY OUTSIDE FACE OF GATE AT EACH SIDE OF GATE GATE LATCH AT BOTTOM RAIL

DUMPSTER ENCLOSURE GATE




DUMPSTER ENCLOSURE NO SCALE

- 1" X 2", 1" X 4", AND 1" X 6" CEDAR FENCE SLATS PLACED 1" APART IN RANDOM ORDER ON BOTH SIDES 6" X 6" X 9'-0" CEDAR POSTS 8'-0" O.C. (TYP.) GALVANIZED STEEL POST ANCHOR SECTION

HARDWARE AND FASTENERS TO BE STAINLESS STEEL

- WATERPROOFING SEALER.



- MAXIMUM SLOPES OF ADJOINING GUTTERS AND ROAD SURFACES IMMEDIATELY ADJACENT TO THE SIDEWALK RAMP OR
 PEDESTRIAN ACCESS ROUTE SHOULD NOT EXCEED 5%. THE MAXIMUM GRADE DIFFERENCE BETWEEN THE GUTTER AND
 CURB RAMP SHALL NOT EXCEED 13%. SEE DETAIL 10 N SHEET 4.
 RAMP GRADE SHALL BE UNIFORM, FREE OF SAGS AND ABRUPT GRADE CHANGES. <u>RUNNING SLOPES OF RAMPS SHALL NOT
 EXCEED 8.3%.</u>
 ALL RAMPS SHALL BE CONSTRUCTED OF CLASS "C" CONCRETE IN ACCORDANCE WITH CONNECTICUT STANDARD
 SPECIFICATIONS.

- EXCEED 8.3%.

 3.ALL RAMPS SHALL BE CONSTRUCTED OF CLASS "C" CONCRETE IN ACCORDANCE WITH CONNECTICUT STANDARD SPECIFICATIONS.

 3.PECIFICATIONS.

 4. SIDEWALK RAMPS SHALL BE CONSTRUCTED OF CLASS "C" CONCRETE IN ACCORDANCE WITH CONNECTICUT STANDARD SPECIFICATIONS.

 5. SIDEWALK RAMPS SHALL BE STABLE, FIRM AND SLIP RESISTANT. SURFACE DISCONTINUITIES SHALL NOT EXCEED "J" (13) MAX. VERTICAL DISCONTINUITIES BETWEEN "J" (6.4) AND "J" (13) MAX. SHALL BE BEVELED 1:2 MINIMUM APPLIED ACROSS THE ENTIRE LEVEL CHANGIOSSINGS SHALL BE WHOLLY CONTAINED WITHIN THE MARKINGS, EXCLUDING APPLIED ACROSS THE ENTIRE LEVEL CHANGIOSSINGS SHALL BE WHOLLY CONTAINED WITHIN THE MARKINGS, EXCLUDING ANY FLARED SIDES. DIAGONAL AND PERPENDICULAR RAMPS SHALL HAVE THE RAMP CLIT PERPENDICULAR TO THE TANCENT OF THE CURB RADIUS FOR THE DESIGNATED ACCESSIBLE ROUTE. BOTH LONGITUDINAL SIDES OF THE RAMP SHOULD BE THE SAME LENGTH, SEVENDE RAMPS SHOULD BE AVOIDED. FLARES ARE NOT CONDERED PART OF PEDESTRIAN ACCESS ROUTE.

 6. REMOVAL OF EXTISTING SIDEWALK FOR NEW RAMP INSTALLATIONS SHALL BE TO THE NEAREST EXPANSION OR CONTRACTION JOINT. B.3% MAXIMUM SLOPE MAY NOT BE ACHIEVABLE DUE TO SIDEWALK GRADE. IN RECOGNITION OF REQUIRED FOR DUMMY JOINTS SHALL BE INCLUDED IN THE COST OF CONCRETE SIDEWALK. PLANES SHALL BE INCLUDED IN THE COST OF CONCRETE SIDEWALK. PLANES SHALL BE INCLUDED IN THE COST OF CONCRETE SIDEWALK. PLANES SHALL BE PARKED IN SHALL BE INCLUDED IN THE COST OF CONCRETE SIDEWALK. PROPERTY OF THE PARKS SAW CUT PREDITED FOR DUMMY JOINTS EXCEED 12' (3658) UNLESS OTHERWISE NOTED.

 7. EXPANSION JOINTS EXCEED 12' (3658) UNLESS OTHERWISE NOTED.

 8. SIDEWALK RAMPS, SHALL BE PAID FOR UNDER THE ITEM "CONCRETE SIDEWALK", INCLUDING DETECTABLE WARNING STRIP AND SIDEWALK CURBING AT THE BACK OF SIDEWALK.

 9. SIDEWALK RAMPS, SHALL BE CONSTRUCTED WITH THE TOE AT THE GUTTER SOF PERPENDICULAR RAMPS UP TO THE OTHER SHALL BE STALL BANDED STRIP AND SIDEWALK CURBING AT THE BACK OF SIDEWALK.

 10. PREFERED LOCATION TO INSTALL DETECTABLE WARNING STRIP SHALL BE 6" (152) FROM THE ED

- SHEET 4.

 TO PERMIT WHEELCHAIR WHEELS TO ROLL BETWEEN DOMES, ALIGN DOMES ON A SQUARE GAID IN THE DIRECTION OF RUNNING SLOPE (PERPENDICULAR TO CURB OR SLOPE BREAK), THE TRANSITION FROM RAMP TO GUTTER SHALL BE FLUSH WITHOUT A LIP.

 FOR SIDEWALKS CONTINUOUS THROUGH DRIVEWAYS, RAMPS AND DETECTABLE WARNING SURFACES ARE NOT REQUIRED. CONSTRUCT A SIDEWALK CURB BEHIND THE SIDEWALK WHEN THERE IS INSUFFICIENT BUFFER AVAILABLE OR WHEN CALLED FOR IN PLANS. SIDEWALK CURB SHALL BE PAID FOR AS PART OF THE ITEM "CONCRETE SIDEWALK" RAMP" OR "CONCRETE SIDEWALK".
- CONCRETE SIDEWALK.

 THE TOP AND BOTTOM OF RAMPS SHOULD BE PROVIDED WITH A 4'x 4'(1219 x 1219) MINIMUM LEVEL LANDING AREA WITH A CROSS SLOPE LESS THAN OR EQUAL TO 2% MAXIMUM IN ANY DIRECTION. DIAGONAL RAMPS SHOULD NOT BE INSTALLED WHERE CURB RADII IS LESS THAN 20'(6096).

 UTILITY POLES, LUMINAIRES, PEDESTRIAN OR SIGNAL POLES, GRATES, ACCESS COVERS, AND OTHER APPURTENANCES SHALL NOT BE LOCATED ON RAMPS, LANDINGS, BLENDED TRANSITIONS, FLARES, AND & GUTTERS WITHIN THE PEDESTRIAN ACCESS ROUTE. GRASS STEIP OR UTILITY STRIP WIDTHS MAY VARY.


 APPROACH SIDEWALK AND LANDING CROSS SLOPE SHALL NOT EXCEED 2%.

 I. THE RUNNING OR CROSS SLOPES ON LANDINGS AT MIDBLOCK CROSSING MAY BE WARPED TO MEET STREET OR HIGHWAY GRADE.


- 18. THE RUNNING OR CROSS SLOPES ON LANDINGS AT MIDBLOCK CROSSING MAY BE WARPED TO MEET STREE! UK HIGHWAY GRADE.

 19. FOR PERPENDICULAR CURB RAMPS A MIN. 4'(1.2m) X 4'(1.2m) TURNING SPACE SHALL BE PROVIDED AT THE TOP OF CURB RAMP, WHERE THE TURNING SPACE IS RESTRICTED AT THE BACK OF SIDEWALK THE TURNING SPACE SHALL BE 4'(1.2m) X 5'(1.5m) WITH THE 5' (1.5m) DIMENSION PROVIDED IN THE DIRECTION OF THE RAMP RUN.

 20. FOR PRAALLE CURB RAMPS, A MIN. 4'(1.2m) X 4'(1.2m) TURNING SPACE SHALL BE PROVIDED AT THE BOTTOM OF CURB RAMP, IF THE TURNING SPACE IS RESTRICTED ON 2 OR MORE SIDES, THE TURNING SPACE SHALL BE 4'(1.2m) X 5'(1.5m) WITH THE 5'(1.5m) DIMENSION PROVIDED IN THE DIRECTION OF THE PEDESTRIAN STREET CROSSING.




SINGLE DIRECTION PERPENDICULAR SIDEWALK RAMP NO / UTILITY GRASS STRIP




DOME SPACING DOME SECTION

STANDARD DOME ON DETECTABLE WARNING TILES



PERPENDICULAR SIDEWALK RAMP W/ 48" (1219) MIN. BY PASS LANDING (TYPE 2)



DANIEL CONLON ARCHITECT 4 Old Mill Road



ENVIRONMENTAL LAND SOLUTIONS, LLC







Baywater Housing

Partners


Darien, CT

26 East Lane

VERIFY SCALE


BAR IS 1 INCH ON

SIDEWALK RAMP DETAILS



- STEEL FOR POSTS SHALL CONFORM TO THE MECHANICAL REQUIREMENTS OF ASTM A 499-81 GRADE 60 AND TO THE CHEMICAL REQUIREMENTS OF ASTM A1-76 CARBON STEEL TEE RAIL HAVING NOMINAL WEIGHT OF 91 LBS. OR GREATER PER LINEAR YARD. 2. AFTER FABRICATION, ALL STEEL POSTS SHALL BE GALVANIZED TO MEET THE REQUIREMENTS OF ASTM A
- 3. ALL SIGN POSTS SHALL HAVE "BREAKAWAY" FEATURES THAT MEET AASHTO, REQUIREMENTS CONTAINED ALL SIGN POSTS SHALL HAVE "BREAKAWAY" FEATURES THAT MEET AASHTO REQUIREMENTS CONTAINED
 IN "STAMDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS FOR HIGHWAY SIGNS, LUMINAIRES AND
 TRAFFIC SIGNALS-1985." THE "BREAKAWAY" FEATURES SHALL BE STRUCTURALLY ADEQUATE TO CARRY
 THE SIGNS SHOWN IN THE PLANS AT 60 MPH WIND LOADINGS. INSTALLATIONS SHALL BE IN
 ACCORDANCE WITH MANUFACTURERS RECOMMENDATIONS.
 TYPE A POSTS - 3 LB/FT TYPE B POSTS - 4 LB/FT.


TYPICAL METAL SIGN POSTS NO SCALE




NOTES

PROCESSED AGGREGATE BASEGRADATION SHALL CONFORM WITH CTDOT, FORM 817, ARTICLE M.05.01-1. COARSE AGGREGATE SHALL CONFORM WITH CTDOT, FORM 817, ARTICLE M.05.01-2(a) (b). THE RECLAIMED MISCELLANEOUS AGGREGATE, ARTICLE M.05.01-2(c) IS NOT ACCEPTABLE.

BITUMINOUS CONCRETE PAVEMENT STANDARD FOR DRIVE AND ON-SITE PARKING
NO SCALE






CONCRETE SIDEWALK DETAIL


SCALES ACCORDINGL

MAY 25, 2018

SITE DETAILS

C5.1





2. DETAILS ON THIS SHEET SHOW STANDARD REINFORCEMENT. WELDED WIRE FABRIC WITH AN AREA EQUAL TO OR GREATER THAN THE REINFORCING SHOWN MAY BE SUBSTITUTED.

3. ALL LAP SPLICES, DEVELOPMENT LENGTHS, BENDS FOR REINFORCEMENT, AND WELDED WIRE FABRIC SHALL CONFORM TO AASHTO STANDARD SPECIFICATIONS FOR HIGHWAY

4. ALL REINFORCEMENT SHALL HAVE A MINIMUM CLEAR COVER OF 2", EXCEPT FOR BENEATH BOTTOM REINFORCEMENT IN TOP SLABS, WHERE THE MINIMUM MAY BE 11/2"

5. MINIMUM CONCRETE COMPRESSIVE STRENGTH FC'=4,000PSI SHALL BE OBTAINED BEFORE

6. BASES AND RISERS AT A DEPTH OF 20' AND GREATER SHALL BE DESIGNED BY THE CONTRACTOR AND WORKING DRAWINGS SHALL BE SUBMITTED TO THE ENGINEER FOR REVIEW.

7. SEE STANDARD DRAWING 507-K FOR CATCH BASIN FRAMES AND GRATES.

8. FOR DOT MAINTENANCE PERSONNEL, RISERS MAY BE PREFABRICATED WITH PIPE OPENINGS IN ALL FOUR WALLS, ADEQUATE REINFORCING AROUND PIPE OPENINGS TO CONFORMING TO THESE PLANS SHALL BE PROVIDED. ANY RISERS USED WHERE A PIPE OPENING IS TO REMAIN IN PLACE MUST BE FORMED UP WITH BRICK AS DIRECTED BY THE

RISERS SHALL NEVER HAVE CORNER PIPE ENTRIES. WHERE THE ALIGNMENT OF THE PIPE WITH RESPECT TO THE CORNER OF THE CATCH BASIN CANNOT BE CHANGED, A ROUND STRUCTURE CONFORMING TO ASTM C478 SHALL BE USED. REINFORCING FOR THE ROUND TOP SLAB WITH A RECTANGULAR OPENING SHALL CONFORM TO DETAILS SHOWN HERE.

CONNECTICUT STANDARD SPECIFICATIONS SECTION M.08.02. IF THE ENGINEER DETERMINES THAT THE CLOSURE OF ANY PIPE OPENING IS UNSATISFACTORY, THE CONTRACTOR SHALL RECLOSE SAID OPENING AT NO ADDITIONAL COST TO THE STATE. KNOCKOUTS FOR PIPE OPENINGS SHALL NOT RESULT IN A REDUCED WALL THICKNESS.


11.THE LATEST STATE OF CONNECTICUT STANDARD SPECIFICATIONS AND SUPPLEMENTALS


13.WALL THICKNESS OF ALL CB'S OVER 10' DEEP SHALL BE INCREASED TO 12" THICK. INSIDE DIMENSION SHALL REMAIN THE SAME. (THE 12" THICKNESS SHALL START AFTER THE FIRST 10")

14.BUTYL RUBBER JOINT SEAL SHALL CONFORM TO AASHTO M-198 AND MORTAR SHALL CONFORM TO THE LATEST STATE OF CONNECTICUT STANDARD SPECIFICATIONS

15. SHRINKAGE AND TEMPERATURE REINFORCEMENT SHALL BE PROVIDED IN THE TOPS OF). SHRINKAGE AND TEMPERATURE REINFORCEMENT SHALL BE PROVIDED IN THE TOPS OF SLABS. THE TOTAL AREA OF REINFORCEMENT PROVIDED SHALL BE AT LEAST 0.125 IN²/FT IN EACH DIRECTION. THE MAXIMUM SPACING OF THIS REINFORCEMENT SHALL NOT EXCEED 18 INCHES.

16.THE DETAILS SHOWN IN THE PLAN VIEW FOR THE PRECAST CONCRETE ROUND STRUCTURES SHALL ALSO BE USED FOR CONVERTING MANHOLES TO CATCH BASINS.







FOR CATCH BASINS IN A LINE OF 6" BITUMINOUS CONCRETE LIP CURBING (MACHINE FORMED)







UNDERDRAIN DETAIL






26 East Lane


Darien, CT


VERIFY SCALE BAR IS 1 INCH ON SCALES ACCORDINGL


STORM DETAILS


C5.2












TYPICAL SANITARY SEWER TRENCH SECTION





MANHOLE RUNG NO SCALE





DANIEL CONLON ARCHITECTS


4 Chill Mill Road












STANDARD 2" METER PIT


- NOTE:


 1. MANUFACTURED BY FORD-ASSOCIATED SUPPLY, MODEL NO.
- PMBB-788-36-48NL.
 VERTICAL CRUSH TO EXCEED 20,000 LBS.
 PROVIDE MOLDED-IN INTERAL ANTI SETTLING FLANGE.




THRUST BLOCK DETAILS

NO SCALE










TYPICAL MJ GATE VALVE INSTALLATION NO SCALE



WATER SERVICE TYPICAL TRENCH DETAIL
NO SCALE

Baywater Housing Partners

26 East Lane


Darien, CT

VERIFY SCALE BAR IS 1 INCH ON IF NOT ONE INCH ON THIS SHEET, ADJUST SCALES ACCORDINGLY

- 1			
	MARK	DATE	DESCRIPTION
- 1	PROJE	CT NO:	B0509-007
	DATE:		MAY 25, 2018
	DILE.	00000000000	OO DETL door

WATER SERVICE DETAILS

C5.6



│ Tighe&Bond

1000 Bridgeport Avenue, Suite 320 Shelton, CT 06484 (203) 712-1100





ENVIRONMENTAL LAND SOLUTIONS, LLC Landscape Architecture and Environmental Planning 8 KNIGHT STREET, SUITE 203 NORWALK, CONNECTICUT 06851

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsllc.net www.elsllc.net



Baywater Housing Partners

26 East Lane

Darien, CT

VERIFY SCALE

BAR IS 1 INCH ON ORIGINAL DRAWING

1 INC.

1 ENCLONE INCH ON

DJECT NO: B0509-007

TE: MAY 25, 2018

E: ELS# 1849

AWN BY: KET


JECKED: MJP

BROWED: KET

LANDSCAPE PLAN

LE: 1" **=** 20'

LP-1



Tighe&Bond

Engineers | Environmental Specialist 1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100

DANIEL CONLON
ARCHITECTS

(203) 544-7888
4 Old Mill Reductions CT 108



ENVIRONMENTAL LAND SOLUTIONS, LLC
Landscape Architecture and Environmental Planning

NORWALK, CONNECTICUT 0

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsilc.net www.elsilc.net

Baywater Housing Partners

26 East Lane

Darien, CT

VERIFY SCALE

BAR IS 1 INCH ON
ORIGINAL DRAWING

1 INC
IF NOT ONE INCH ON
THIS SHEET, ADJUST
SCALES ACCORDINGLY


MARK DATE DESCRIPTION
PROJECT NO:
DATE: 5-25-1:
FILE:
DRAWN BY:
CHECKED:
APPROVED:

A-1

1/4" = 1'-0"

1st FLOOR

SCALE: 14" = 1-0" 0 2' 4'



Tighe&Bond
Engineers | Environmental Specialists
1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100





ENVIRONMENTAL LAND SOLUTIONS, LLC

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsilic.net www.elsilic.net

Baywater Housing **Partners**


26 East Lane

Darien, CT

VERIFY SCALE BAR IS 1 INCH ON ORIGINAL DRAWING

1 INCH ON IF NOT ONE INCH ON THIS SHEET, ADJUST SCALES ACCORDINGLY

	E:	1/4" =	1'-0'				
APPRO'	VED:						
CHECK	ED:						
DRAWN BY:							
FILE:							
DATE:		5-25-18					
PROJE	CT NO:						
MARK	DATE	DESCRIPTION					



Tighe&Bond

Engineers | Environmental Specialist 1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100





ENVIRONMENTAL LAND SOLUTIONS, LLC Landscape Architecture and Environmental Planning

> 8 KNIGHT STREET, SUITE 20 NORWALK, CONNECTICUT 068

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsilic.net www.elsilic.net

Baywater Housing Partners

26 East Lane

Darien, CT

VERIFY SCALE

BAR IS 1 INCH ON
ORIGINAL DRAWING

O 1 1 INCH
IF NOT ONE INCH ON
THIS SHEET, ADJUST
SCALES ACCORDINGLY

MARK	DATE	DESCRIPTION				
PROJEC	T NO:					
DATE:		5-25-18				
FILE:						
DRAWN BY:						
CHECK	ED:					
APPRO	/ED:					
SCALE	≣ :	1/4"	=	1'-0"		
		A-3				







2 LEFT ELEVATION

SCALE: 14' = 1-0'

Delta 2' 4'

Tighe&Bond

Engineers | Environmental Specialist 1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100

DANIEL CONLON

A R C H I T E C T S

(203) 544-788 4 Old Mill Road

(2021) 544-788 4 Old Mill Road

(2021) 644-788 5 Only Road 1 Old Mill Road



ENVIRONMENTAL LAND SOLUTIONS, LLC Landscape Architecture and Environmental Planning

> 8 KNIGHT STREET, SUITE 20 NORWALK, CONNECTICUT 068

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsilic.net www.elsilic.net

Baywater Housing Partners

26 East Lane

Darien, CT


VERIFY SCALE

BAR IS 1 INCH ON ORIGINAL DRAWING

1 INCH
IF NOT ONE INCH ON THIS SHEET, ADJUST SCALES ACCORDINGLY

MARK	DATE	DESCRIPTION		
PROJE	CT NO:			
DATE:		5-25-18		
FILE:				
DRAW	N BY:			
CHECK	ED:			
APPRO	VED:			
SCAL	E:	1/4"	=	1'-0

A-4



Tighe&Bond

1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100

DANIEL CONLON ARCHITECTS



ENVIRONMENTAL LAND SOLUTIONS, LLC

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsilic.net www.elsilic.net

Baywater Housing **Partners**

26 East Lane


Darien, CT

VERIFY SCALE BAR IS 1 INCH ON ORIGINAL DRAWING

MARK	DATE	DESCRIPTION		
PROJE	CT NO:			
DATE:		5-25-18		
FILE:				
DRAW	N BY:			
CHECK	ED:			
APPRO	VED:			
SCAL	E:	1/4"	=	1'-0"

B-1

1st FLOOR



Tighe&Bond
Engineers | Environmental Specialists
1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100





ENVIRONMENTAL LAND SOLUTIONS, LLC

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsilic.net www.elsilic.net

Baywater Housing **Partners**

26 East Lane

Darien, CT

VERIFY SCALE BAR IS 1 INCH ON ORIGINAL DRAWING

1 INCH ON IF NOT ONE INCH ON THIS SHEET, ADJUST SCALES ACCORDINGLY

MARK DATE PROJECT NO:	E	DESCRIP		_
	E	DESCRIP		_
	E	DESCRIP		
	E	DESCRIP		_
	E	DESCRIP		
	E	DESCRIP		
PROJECT NO:			TION	
DATE:		5-	25-18	
FILE:				
DRAWN BY:				
CHECKED:				
APPROVED:				

B-2

2nd FLOOR

SCALE: 1/4' = 1-0' 0 2' 4' 8'



FRONT ELEVATION

SCALE: 14" = 1"-0"

0 2 4"



RIGHT ELEVATION

SCALE 1/4" = 1-0"

2 4

Tighe&Bond

Engineers | Environmental Specialist 1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100





ENVIRONMENTAL LAND SOLUTIONS, LLC Landscape Architecture and Environmental Planning

8 KNIGHT STREET, SUITE 20 NORWALK, CONNECTICUT 068

Tel: (203) 855-7879 Fax: (203) 855-7836 info@elsilic.net www.elsilic.net

Baywater Housing Partners

26 East Lane

Darien, CT

VERIFY SCALE

BAR IS 1 INCH ON ORIGINAL DRAWING

1 INCH
IF NOT ONE INCH ON THIS SHEET, ADJUST SCALES ACCORDINGLY

MARK	DATE	DESCRIPTION	
PROJE	CT NO:	•	
DATE:		5-25-18	
FILE:			
DRAW	N BY:		
CHECK	ED:		
APPRO	VED:		
SCAL	E:	1/4"	=

B-3







2 LEFT ELEVATION

SCALE: 14" = 7-0"

0 2 4 8

Tighe&Bond

Engineers | Environmental Specialist 1000 Bridgeport Avenue Suite 320 Shelton, CT 06484 (203) 712-1100

DANIEL CONLON A R C H I T E C T S (203) 544-7888 4 Old MII Road docinolarachitects.com 4 Old MII Road



ENVIRONMENTAL LAND SOLUTIONS, LLC Landscape Architecture and Environmental Planning

8 KNIGHT STREET, SUITE 20 NORWALK, CONNECTICUT 068

Tel: (203) 855-7879 Fax: (203) 855-7836 info@eislic.net www.eislic.net

Baywater Housing Partners

26 East Lane

Darien, CT

VERIFY SCALE

BAR IS 1 INCH ON ORIGINAL DRAWING

1 INCH IF NOT ONE INCH ON THIS SHEET, ADJUST SCALES ACCORDINGLY

MARK	DATE	DESCRIPTION		
PROJEC	T NO:			
DATE:		5-25-18		
FILE:				
DRAWN	BY:			
CHECKE	D:			
APPROV	ED:			
SCALE	:	1/4"	=	1'-0'

nes/Shared/Current Jobs DCA/Genovese East Lane 1516/Drawing files/ArchiCA